

PRODUCT CERTIFICATION

HEAT NUMBER

SALES ORDER

SOLD TO

SHIP TO

| CUSTOMER P.O. | P.O. LINE # | CUSTOMER PART | QUANTITY | BNDLS | LADING NO | SHIPMENT DATE |
|---|-------------|---------------|----------|-------|------------|---------------|
| | 003 | | 5,274 FT | 9 | 0085095214 | 02/18/2021 |
| SPECIFICATION EDTRN20000.2500-9003 | | | | | | |
| Grade 1026AK | | | | | | |
| O.D. 2.0000 +0.0060 - 0.0000 | | | | | | |
| I.D. 1.5000 +0.0000 -0.0060 | | | | | | |
| Wall .2500 +0.0000 -0.0000 *Reference Dimension | | | | | | |
| Len 20' 0.000"/24' 0.000" Random | | | | | | |
| Temp Stress Relieved | | | | | | |
| ASTM A-513 Type 5 Drawn Over Mandrel (DOM) | | | | | | |
| Cold Drawn Electric Weld Carbon Steel Round Mechanical Tubing | | | | | | |
| WT/FT: 4.67250 | | | | | | |
| SPC Required: None | | | | | | |
| Finish Type: Normal | | | | | | |
| End Use: None | | | | | | |
| ***** STENCIL REQUIRED ***** | | | | | | |
| PHYSICAL TESTS REQUIRED | | | | | | |
| TENSILE: 75000 / 115000 | | | | | | |
| YIELD: 65000 / 105000 | | | | | | |
| YT: .99 MAXIMUM | | | | | | |
| RB: 80 / 100 | | | | | | |
| ELONG: 10 / 40 | | | | | | |
| Weight: 24891 LBS | | | | | | |
| CERTIFICATION REQUIREMENTS | | | | | | |
| Chemical, Ladle Analysis, % | | | | | | |
| | | | | | | |

PRODUCT CERTIFICATION

HEAT NUMBER

SALES ORDER

SOLD TO

SHIP TO

| CUSTOMER P.O. | P.O. LINE # | CUSTOMER PART | QUANTITY | BNDLS | LADING NO | SHIPMENT DATE |
|--|-------------|---------------|----------|-------|------------|---------------|
| | 002 | | 2,414 FT | 4 | 0085096250 | 04/02/2021 |
| SPECIFICATION EDTRN20000.2500-9003 | | | | | | |
| Grade 1026AK | | | | | | |
| O.D. 2.0000 +0.0060 - 0.0000 | | | | | | |
| I.D. 1.5000 +0.0000 -0.0060 | | | | | | |
| Wall .2500 +0.0000 -0.0000 *Reference Dimension | | | | | | |
| Len 20' 0.000"/24' 0.000" Random | | | | | | |
| Temp Stress Relieved | | | | | | |
| ASTM A-513 Type 5 Drawn Over Mandrel (DOM) | | | | | | |
| Cold Drawn Electric Weld Carbon Steel Round Mechanical Tubing | | | | | | |
| WT/FT: 4.67250 | | | | | | |
| SPC Required: None | | | | | | |
| Finish Type: Normal | | | | | | |
| End Use: None | | | | | | |
| ***** STENCIL REQUIRED ***** | | | | | | |
| Stencil Must Include: | | | | | | |
| STANDARD STENCIL FIELDS | | | | | | |
| PHYSICAL TESTS REQUIRED | | | | | | |
| TENSILE: 75000 / 115000 | | | | | | |
| YIELD: 65000 / 105000 | | | | | | |
| YT: .99 MAXIMUM | | | | | | |
| RB: 80 / 100 | | | | | | |
| ELONG: 10 / 40 | | | | | | |
| Weight: 11391 LBS | | | | | | |
| CERTIFICATION REQUIREMENTS | | | | | | |
| Chemical, Ladle Analysis, % | | | | | | |